

Prairielands Council Pinewood Derby Rules (New Changes as of 2015)

BODY SPECS:

R1.

- A. Width - Not to exceed 2 3/4 inches
- B. Length - Not over 7 inches
- C. Wheelbase – No More than 4 3/8 inches from center of front axle slot to center of rear axle slot, 7/8 from one end of body and 1 3/4 from the other end of body (normal slot location but axle holes may be drilled, you do not have to use the slots). **Cannot extend wheelbase.**
- D. Weight - Not over 5 ounces on scale accurate to 1/10 ounce (141.75 grams).
- E. Height - Not to exceed 4 inches.
- F. Center Rail Width Clearance – At least 1 3/4 inches minimum along entire center length of car.
- G. Bottom Clearance - at least 3/8 inches from track, as long as it doesn't rub the track. Fender flairs with less clearance are acceptable as long as the center rail width clearance is the same in rule R1E.

R2. Body design may be enhanced by adding other stable materials such as plastic or metal. All additions must be firmly attached and conform to the size specifications. No part of the car body may protrude in front of the starting peg.

R3. The following items are PROHIBITED:

- A. Springs
- B. Starting devices or propellants
- C. Electronic or lighting devices
- D. Liquids, wet paint, oil, sticky substance, or powders of any kind (other than axle lubrication)
- E. Glass or excessively fragile parts
- F. Wheel bearings
- G. Loose objects on car
- H. Magnets/Mercury

WHEELS:

R4. BSA wide wheels are required. Outer wheel surface may be lightly sanded, shaved, or polished to remove surface imperfections and mold casting burrs, but must not be reshaped in any way in an attempt to lighten the wheel, minimize tread contact or alter aerodynamics. The fluting/ridge marks at outer edge of wheel and all other BSA markings on the inside & outside wheel area must remain visible. Wheel hub may be coned and polished.

R5. The following wheel modifications are PROHIBITED:

- A. Rounding of wheel edges
- B. Grooving, H-cutting or V-cutting
- C. Altering of wheel profile
- D. Narrowing the tread surface
- E. Drilling sidewalls

R6. There must be four wheels on the car, however, **it is not required that all four wheels make contact** with the track surface. The wheels must be attached directly to axle and spin freely and oriented on side of car in area of normal slot location (but holes may be drilled and you do not have to use slots) - must meet wheelbase standard in rule R1C above for all 4 wheels.

AXLES:

R7. Axles must be used from the BSA Pinewood Derby Kit and can be de-burred, sanded and beveled for performance. Axles must not be connected to any device that mechanically alters rotation and spin.

R8. Only dry graphite may be used for lubricant. Do not get carried away with graphite so track will stay relatively clean.